

# CLEVELAND



## ABOUT

Equinix is located within the Sterling building. We are in the heart of downtown, approximately 1/2 mile from the Tandem switch. The Equinix Cleveland data center offers 7,000 square feet of co-location space with multiple connectivity options and several layers of security.

## LOCATION

1255 Euclid Avenue  
the Sterling Building  
Cleveland, OH 44115, USA

## PROFILE

**Phone** – 1.888.892.0607 (USA or Canada)  
or 1.650.513.7600 (outside USA or Canada)  
**Email** – support@equinix.com

## POWER

**Power Density** – 2.4KW Max (utilization)

**UPS System** – 405 KW UPS System, System is deployed as N, UPS Battery backup systems are deployed to carry full design load for 15 minutes, UPS distribution systems support 405 KW primary with 30% additional for redundant circuits.

**DC Plant** – 60 KW DC System, System is deployed as 2N with dedicated A&B plants, DC Battery backup system are designed and deployed to carry full load for 2 hours per each plant, DC distribution systems support 60 KW primary with 30% additional for redundant circuits.

**Standby Generators** – 750 KW generator systems, System is deployed as N, Dedicated fuel system designed and deployed to sustain continuous operation at full design load for 24 hours.

## FIBER

**Fiber Conduits** – Seven 4 inch conduits and six 2 inch conduits

**Fiber Innerducts** – Twenty-seven innerducts, four - 1 inch innerducts/ conduit

## TELCO INFORMATION

**NPA/NXX** – 216-685

## ENVIRONMENT

**Fire Suppression** – Pre-Action double interlock fire suppression system, dual zoned smoke and heat fire alarm detection system, dry Pipe water based system, cross zone releasing function (three events must occur for full release)

**HVAC** – 281 KW of Heat Rejection Capacity, System is deployed as N+1, A/C units maintain a climate of 70 degrees (+/- 5) and 30-60% humidity, (SLA Statement)

**Alarm Monitoring** – All essential equipment is tied into Falcon Alarm System (UPS, DC plant, PMM's, BDCBB's, ATS's, Generators, Diesel Tanks, TVSS, Fire system), Operations Alarm Management (OAM) Group Monitors facility falcon units 24/7/365, Alarming is a dry contact system set to normally closed.

## CLEVELAND

### FLOOR LOAD

100 psft

### CEILING HEIGHT

Fourteen feet above raised floor

### ROOF RIGHTS

Roof rights available with satellite space

### LINE OF SIGHT

Clear line of sight to the North and East

### SQUARE FOOTAGE

Colocation Area - 12,098 sq. ft.

### KVM CART

KVM cart available upon request

### PRODUCT AVAILABILITY

Cage Space available  
Cabinets Available  
UPS Power Available  
DC Power Available  
Standard Cross Connects – DS0, DS1, DS3,  
Ethernet, Fiber  
SingleCNXT-i (Internet Access)  
TechSmart (remote hands): 24/7/365  
Technical Support  
Network Timing

### SECURITY

**Security Systems** – Card access control at all secure areas/doors, Surveillance cameras at strategic locations, exterior and interior CCTV coverage, 24/7 Corporate security surveillance, Speaker and Phone system installed throughout facility for correspondence with local and remote security personnel, 30 days of on-site video back-up

### EQUINIX MMR

AFS (American Fiber Systems), Cavalier Networks, E-xpedient, Fidelity Access Networks, ICG Telecom Group, MCI, OneCleveland, Qwest, SBC, SingleCNXT, The T1 Company