

DETROIT



ABOUT

The Equinix Detroit data center is a one-story building just 300 feet from SBC and the relay station. This site features 12,000 square feet of colocation space and multiple connectivity options..

LOCATION

24660 Lahser Road
Southfield, MI, 48034, USA

PROFILE

Phone – 1.888.892.0607 (USA or Canada)
or 1.650.513.7600 (outside USA or Canada)
Email – support@equinix.com

POWER

Power Density – 2.4KW Max (utilization)

UPS System – 405 KW UPS System, System is deployed as N, UPS Battery backup systems are deployed to carry full design load for 15 minutes, UPS distribution systems support 405 KW primary with 30% additional for redundant circuits.

DC Plant – 60 KW DC System, System is deployed as 2N with dedicated A&B plants, DC Battery backup system are designed and deployed to carry full load for 2 hours per each plant, DC distribution systems support 60 KW primary with 30% additional for redundant circuits.

Standby Generators – 750 KW generator systems, dedicated fuel system designed and deployed to sustain continuous operation at full design load for 24 hours

FIBER

Fiber Diversity – Two fiber entry points
Fiber Conduits – Twelve 4-inch conduits
Fiber Innerducts – Forty-eight innerducts, four 1-inch innerducts per conduit

TELCO INFORMATION

NPA/NXX – 248-353

ENVIRONMENT

Fire Suppression – Pre-Action double interlock fire suppression system, dual zoned smoke and heat fire alarm detection system, dry Pipe water based system, cross zone releasing function (three events must occur for full release) reaction, dry pipe sprinkler system

HVAC – 281 KW of Heat Rejection Capacity, System is deployed as N+1, A/C units maintain a climate of 70 degrees (+/- 5) and 30-60% humidity, (SLA Statement)

Alarm Monitoring – All essential equipment is tied into Falcon Alarm System (UPS, DC plant, PMM's, BDCBB's, ATS's, Generators, Diesel Tanks, TVSS, Fire system), Operations Alarm Management (OAM) Group Monitors facility falcon units 24/7/365, Alarming is a dry contact system set to normally closed.

DETROIT

FLOOR LOAD

100 psft

CEILING HEIGHT

Nine feet three inches above raised floor

ROOF RIGHTS

Roof rights available

LINE OF SIGHT

Clear line of sight in all directions

SQUARE FOOTAGE

Colocation Area - 12,000 sq. ft.

KVM CART

KVM cart available upon request

PRODUCT AVAILABILITY

Cage Space available
Cabinets Available
UPS Power Available
DC Power Available
Standard Cross Connects – DS0, DS1, DS3,
Ethernet, Fiber
SingleCNXT-i (Internet Access)
TechSmart (remote hands): 24/7/365
Technical Support

SECURITY

Security Systems – Card access control at all secure areas/doors, Surveillance cameras at strategic locations, exterior and interior CCTV coverage, 24/7 Corporate security surveillance, Speaker and Phone system installed throughout facility for correspondence with local and remote security personnel, 30 days of on-site video back-up

EQUINIX MMR

Cogent, Easy Online Solutions, Level (3), McLeodUSA, SBC, SingleCNXT, US Signal