

LOS ANGELES



ABOUT

The Equinix Los Angeles data center is a 17,927 square foot facility offering collocation and interconnection.

LOCATION

1200 West 7th Street,
Los Angeles, CA 90017, USA

PROFILE

Phone – 1.888.892.0607 (USA or Canada)
or 1.650.513.7600 (outside USA or Canada)
Email – support@equinix.com

POWER

Power Density – 2.4KW Max (utilization)

UPS System – 315 KW UPS System, System is deployed as N, UPS Battery backup systems are deployed to carry full design load for 15 minutes, UPS distribution systems support 315 KW primary with 30% additional for redundant circuits.

DC Plant – 115 KW DC System, System is deployed as 2N with dedicated A&B plants, DC Battery backup system are designed and deployed to carry full load for 2 hours per each plant, DC distribution systems support 115 KW primary with 30% additional for redundant circuits.

Standby Generators – 750 KW generator systems (Building owned), Dedicated fuel system designed and deployed to sustain continuous operation at full design load for 24 hours .

TELCO INFORMATION

NPA/NXX – 213 - 228, 327, 538, 553, 612, 861, 955

ENVIRONMENT

Fire Supression – Pre-Action double interlock fire suppression system, dual zoned smoke and heat fire alarm detection system, dry Pipe water based system, cross zone releasing function (three events must occur for full release) reaction, dry pipe sprinkler system

HVAC – 165 KW of Heat Rejection Capacity, System is deployed as N+1, A/C units maintain a climate of 70 degrees (+/- 5) and 30-60% humidity, (SLA Statement)

Alarm Monitoring – All essential equipment is tied into Falcon Alarm System (UPS, DC plant, PMM's, BDCBB's, ATS's, Generators, Diesel Tanks, TVSS, Fire system), Operations Alarm Management (OAM) Group Monitors facility falcon units 24/7/365, Alarming is a dry contact system set to normally closed.



LOS ANGELES

FLOOR LOAD

100 psf

CEILING HEIGHT

Twelve feet above raised floor

ELEVATORS

Weight capacity at 4,500 pounds with 6x9 floor size

ROOF RIGHTS

Roof rights available with satellite space

LINE OF SIGHT

Obstructed view to the north and east

SQUARE FOOTAGE

Colocation Area - 17,927 sq. ft.

KVM CART

KVM cart available upon request

PRODUCT AVAILABILITY

Cage Space available
Cabinets Available
UPS Power Available
DC Power Available
Standard Cross Connects – DS0, DS1, DS3,
Ethernet, Fiber
SingleCNXT-i (Internet Access)
TechSmart (remote hands): 24/7/365
Technical Support
Network Timing

SECURITY

Security Systems – Card access control at all secure areas/doors, Surveillance cameras at strategic locations, exterior and interior CCTV coverage, 24/7 Corporate security surveillance, Speaker and Phone system installed throughout facility for correspondence with local and remote security personnel, 30 days of on-site video back-up

EQUINIX MMR

AT&T Local, Cogent Communications, Global Crossing, Internap, KMC Telecom, Level (3), Limelight Networks, MCI, MegaPath, Mzima, OnFiber Communications, Qwest, SBC, SingleCNXT, Telecom New Zealand, Wilshire Connection, WilTel, XO Communications

