

# MIAMI - METRO MALL



## ABOUT

Equinix has two locations in Miami, both within the Miami Central Business District. We're located at 1 NE First Street (the Metro Mall) and at 36 NE Second Street. The Equinix 1 NE First Street data center is located in an eight-story concrete building, also known as the Metro Mall. At this location, we offer 15,000 square feet of colocation space with multiple connectivity options. Customers benefit from fiber diversity and access to roof rights with satellite space available.

## LOCATION

1 NE 1st Street  
Miami, FL 33132, USA

## PROFILE

**Phone** – 1.888.892.0607 (USA or Canada)  
or 1.650.513.7600 (outside USA or Canada)  
**Email** – support@equinix.com

## POWER

**Power Density** – 2.4KW Max (utilization)

**UPS System** – 120 KW UPS System, System is deployed as N, UPS Battery backup systems are deployed to carry full design load for 15 minutes, UPS distribution systems support 120 KW primary with 30% additional for redundant circuits.

**DC Plant** – 230 KW DC System, System is deployed as 2N with dedicated A&B plants, DC Battery backup system are designed and deployed to carry full load for 2 hours per each plant, DC distribution systems support 230 KW primary with 30% additional for redundant circuits.

**Standby Generators** – 1000 KW generator systems, Dedicated fuel system designed and deployed to sustain continuous operation at full design load for 24 hours.

## FIBER

**Fiber Entry Points** – 2

**Fiber Conduits** – Eight 4-inch conduits

**Fiber Innerducts** – Thirty-two innerducts, four 1-inch innerducts/conduit

## TELCO INFORMATION

**NPA/NXX** – 305-358

## ENVIRONMENT

**Fire Suppression** – Pre-Action double interlock fire suppression system, dual zoned smoke and heat fire alarm detection system, dry Pipe water based system, cross zone releasing function (three events must occur for full release) re-action, dry pipe sprinkler system

**HVAC** – 739 KW of Heat Rejection Capacity, System is deployed as N+1, A/C units maintain a climate of 70 degrees (+/- 5) and 30-60% humidity, (SLA Statement)

**Alarm Monitoring** – All essential equipment is tied into Falcon Alarm System (UPS, DC plant, PMM's, BDCBB's, ATS's, Generators, Diesel Tanks, TVSS, Fire system), Operations Alarm Management (OAM) Group Monitors facility falcon units 24/7/365, Alarming is a dry contact system set to normally closed.



## MIAMI - METRO MALL

### FLOOR LOAD

125 psf

### CEILING HEIGHT

Ten feet above raised floor

### ELEVATORS

Weight capacity at 2,400 pounds with dimensions of 7x8x7, top of cage can be removed for taller objects

### ROOF RIGHTS

Roof rights available with satellite space

### LINE OF SIGHT

Obstructed views in all directions except to the southwest and southeast

### SQUARE FOOTAGE

Colocation Area - 15,000 sq. ft.

### KVM CART

KVM cart available upon request

### PRODUCT AVAILABILITY

Cage Space available  
Cabinets Available  
UPS Power Available  
DC Power Available  
Standard Cross Connects – DS0, DS1, DS3,  
Ethernet, Fiber  
SingleCNXT-i (Internet Access)  
TechSmart (remote hands): 24/7/365  
Technical Support  
Network Timing

### SECURITY

**Security Systems** – Card access control at all secure areas/doors, Surveillance cameras at strategic locations, exterior and interior CCTV coverage, 24/7 Corporate security surveillance, Speaker and Phone system installed throughout facility for correspondence with local and remote security personnel, 30 days of on-site video back-up

### EQUINIX MMR

BellSouth, Cogent Communications, E-xpedient, EPIK Communications, KMC Telecom, Level (3), MCI, OnFiber Communications, PCCW Global, Progress Telecom, SingleCNXT, XO Communications, Xspedius (ACSI)

