

MIAMI - SECOND STREET



ABOUT

Equinix has two locations in Miami, both within the Miami Central Business District. We're located at 1 NE First Street (the Metro Mall) and at 36 NE Second Street. The Equinix 36 NE Second Street data center offers colocation, and interconnection. This site offers nearly 16,000 square feet of space, multiple connectivity options, and several layers of security.

LOCATION

36 NE Second Street
Miami, FL 33132, USA

PROFILE

Phone – 1.888.892.0607 (USA or Canada)
or 1.650.513.7600 (outside USA or Canada)
Email – support@equinix.com

POWER

Power Density – 2.4KW Max (utilization)

UPS System – 360 KW UPS System, System is deployed as N, UPS Battery backup systems are deployed to carry full design load for 15 minutes, UPS distribution systems support 360 KW primary with 30% additional for redundant circuits.

DC Plant – 30 KW DC System, System is deployed as 2N with dedicated A&B plants, DC Battery backup system are designed and deployed to carry full load for 2 hours per each plant, DC distribution systems support 30 KW primary with 30% additional for redundant circuits.

Standby Generators – 750 KW generator systems, Dedicated fuel system designed and deployed to sustain continuous operation at full design load for 24 hours

FIBER

Fiber Entry Points – 2

TELCO INFORMATION

NPA/NXX – 305-374

ENVIRONMENT

Fire Suppression – Pre-Action double interlock fire suppression system, dual zoned smoke and heat fire alarm detection system, dry Pipe water based system, cross zone releasing function (three events must occur for full release) reaction, dry pipe sprinkler system

HVAC – 380 KW of Heat Rejection Capacity, System is deployed as N+1, A/C units maintain a climate of 70 degrees (+/- 5) and 30-60% humidity, (SLA Statement)

Alarm Monitoring – All essential equipment is tied into Falcon Alarm System (UPS, DC plant, PMM's, BDCBB's, ATS's, Generators, Diesel Tanks, TVSS, Fire system), Operations Alarm Management (OAM) Group Monitors facility falcon units 24/7/365, Alarming is a dry contact system set to normally closed.

MIAMI - SECOND STREET

FLOOR LOAD

125 psf

CEILING HEIGHT

Eleven feet above raised floor

ELEVATORS

Weight capacity at 3,500 pounds; dimensions at 8x5x7 feet

ROOF RIGHTS

Roof rights available

LINE OF SIGHT

Clear line of sight to the east, south and north with limited visibility to the west

SQUARE FOOTAGE

Colocation Area - 17,545 sq. ft.

KVM CART

KVM cart available upon request

PRODUCT AVAILABILITY

Cage Space available
Cabinets Available
UPS Power Available
DC Power Available
Standard Cross Connects – DS0, DS1, DS3,
Ethernet, Fiber
SingleCNXT-i (Internet Access)
TechSmart (remote hands): 24/7/365
Technical Support

SECURITY

Security Systems – Card access control at all secure areas/doors, Surveillance cameras at strategic locations, exterior and interior CCTV coverage, 24/7 Corporate security surveillance, Speaker and Phone system installed throughout facility for correspondence with local and remote security personnel, 30 days of on-site video back-up

EQUINIX MMR

BellSouth, Cogent, Expedient, FPL
Fibernet, Global Crossing, Level (3), MCI,
OnFiber, Progress Telecom, Qwest, SAV-
VIS, SingleCNXT, Telcove, WilTel, XO,
Xspedius