

NEW YORK CITY - 60 HUDSON



ABOUT

Equinix has three locations in New York City including 111 Eighth Avenue, 60 Hudson and 65 Broadway.

The Equinix 65 Broadway data center is located in a 21-story steel concrete encased frame building one block south of Wall Street, in the heart of New York's Financial District. The site is located less than 1/2 mile from the 60 Hudson carrier hotel and approximately two miles from the 111 Eighth Avenue carrier hotel. The building was construction in 1917 and offers 15,000 square feet of colocation space and multiple connectivity options.

LOCATION

65 Broadway
New York, NY 10006, USA

PROFILE

Phone – 1.888.892.0607 (USA or Canada)
or 1.650.513.7600 (outside USA or Canada)
Email – support@equinix.com

POWER

Power Density – 2.4KW Max (utilization)

UPS System – 248 KW UPS System, System is deployed as N, UPS Battery backup systems are deployed to carry full design load for 15 minutes, UPS distribution systems support 248 KW primary with 30% additional for redundant circuits.

DC Plant – 58 KW DC System, System is deployed as 2N with dedicated A&B plants, DC Battery backup system are designed and deployed to carry full load for 2 hours per each plant, DC distribution systems support 58 KW primary with 30% additional for redundant circuits.

Standby Generators – 750 KW generator systems, System is deployed as N, Dedicated fuel system designed and deployed to sustain continuous operation at full design load for 24 hours.

FIBER

of Fiber Entry Points – 2
Fiber Conduits – Eight 4-inch conduits located on each side of the building
Fiber Innerducts – Thirty-two innerducts, four 1-inch innerducts/conduit

TELCO INFORMATION

NPA/NXX – 212-430

ENVIRONMENT

Fire Supression – Pre-Action double interlock fire suppression system, dual zoned smoke and heat fire alarm detection system, dry Pipe water based system, cross zone releasing function (three events must occur for full release) re-action, dry pipe sprinkler system

HVAC – 317 KW of Heat Rejection Capacity, System is deployed as N+1, A/C units maintain a climate of 70 degrees (+/- 5) and 30-60% humidity, (SLA Statement)

Alarm Monitoring – All essential equipment is tied into Falcon Alarm System (UPS, DC plant, PMM's, BDCBB's, ATS's, Generators, Diesel Tanks, TVSS, Fire system), Operations Alarm Management (OAM) Group Monitors facility falcon units 24/7/365, Alarming is a dry contact system set to normally closed.

NEW YORK CITY - 60 HUDSON

FLOOR LOAD

100 psf

FLOORS

Raised floors with forced air

CEILING HEIGHT

Eleven feet above raised floor

ELEVATORS

Weight capacity at 3,500 pounds

ROOF RIGHTS

Roof rights available

LINE OF SIGHT

Clear line of sight to the east, south, and west

SQUARE FOOTAGE

Colocation Area - 16,853 sq. ft.

KVM CART

KVM cart available upon request

PRODUCT AVAILABILITY

Cage Space available
Cabinets Available
UPS Power Available
DC Power Available
SingleCNXT-i (Internet Access)
TechSmart (remote hands): 24/7/365
Technical Support

SECURITY

Security Systems – Card access control at all secure areas/doors, Surveillance cameras at strategic locations, exterior and interior CCTV coverage, 24/7 Corporate security surveillance, Speaker and Phone system installed throughout facility for correspondence with local and remote security personnel, 30 days of on-site video back-up

EQUINIX MMR

AT&T Local, Cablevision Lightpath, ConEdison Communications, Level (3), MCI, Qwest, SingleCNXT, Verizon, XO Communications, Yipes Communications