

NASHVILLE



ABOUT

Equinix Nashville is located at 147 Fourth Avenue. This data center offers nearly 20,000 square feet of colocation space with multiple connectivity options. Sophisticated fire suppression and power redundancy units are in place to ensure customer equipment is not compromised.

LOCATION

147 Fourth Avenue
SunTrust Parking Garage
Nashville, TN 37219, USA

PROFILE

Phone – 1.888.892.0607 (USA or Canada)
or 1.650.513.7600 (outside USA or Canada)
Email – support@equinix.com

POWER

Power Density – 2.4KW Max (utilization)

UPS System – 120 KW UPS System, System is deployed as N, UPS Battery backup systems are deployed to carry full design load for 15 minutes, UPS distribution systems support 120 KW primary with 30% additional for redundant circuits.

DC Plant – 115 KW DC System, System is deployed as 2N with dedicated A&B plants, DC Battery backup system are designed and deployed to carry full load for 2 hours per each plant, DC distribution systems support 115 KW primary with 30% additional for redundant circuits.

Standby Generators – 1250 KW generator systems, Dedicated fuel system designed and deployed to sustain continuous operation at full design load for 24 hours

FIBER

of Fiber Entry Points – 2
Fiber Conduits – Eight 4-inch conduits
Fiber Innerducts – Thirty-two innerducts, four 1-inch innerducts/conduit

TELCO INFORMATION

NPA/NXX – 615/460

ENVIRONMENT

Fire Suppression – Pre-Action double interlock fire suppression system, dual zoned smoke and heat fire alarm detection system, dry Pipe water based system, cross zone releasing function (three events must occur for full release) re-action, dry pipe sprinkler system

HVAC – 840 KW of Heat Rejection Capacity, System is deployed as N+1, A/C units maintain a climate of 70 degrees (+/- 5) and 30-60% humidity, (SLA Statement)

Alarm Monitoring – All essential equipment is tied into Falcon Alarm System (UPS, DC plant, PMM's, BDCBB's, ATS's, Generators, Diesel Tanks, TVSS, Fire system), Operations Alarm Management (OAM) Group Monitors facility falcon units 24/7/365, Alarming is a dry contact system set to normally closed.

NASHVILLE

FLOOR LOAD

150 psf

CEILING HEIGHT

Fifteen feet above raised floor

ELEVATORS

Weight capacity at 5,000 pounds with dimensions of 9.5 x 4.5 x 8

ROOF RIGHTS

Roof rights available with satellite space

LINE OF SIGHT

Obstructed view to the south

SQUARE FOOTAGE

Colocation Area - 19,656 sq. ft.

KVM CART

KVM cart available upon request

PRODUCT AVAILABILITY

Cage Space available
Cabinets Available
UPS Power Available
DC Power Available
Standard Cross Connects – DS0, DS1, DS3,
Ethernet, Fiber
TechSmart (remote hands): 24/7/365
Technical Support

SECURITY

Security Systems – Card access control at all secure areas/doors, Surveillance cameras at strategic locations, exterior and interior CCTV coverage, 24/7 Corporate security surveillance, Speaker and Phone system installed throughout facility for correspondence with local and remote security personnel, 30 days of on-site video back-up

EQUINIX MMR

American Fiber Systems, BellSouth, SingleCNXT-i