

SEATTLE - 1914 3RD



ABOUT

Equinix has two data centers in Seattle. We are at 1914 Third Avenue and at 2001 Sixth Avenue (The Westin Building). Equinix's Third Avenue data center is a 24 X 7 - manned, 29,000 square foot facility with numerous connectivity options. The building is a seismic rating Zone 3 with diverse entrance facilities for fiber. This Seattle data center has a spacious conference room with Internet access available to customers as well as a customer staging area complete with Internet access, workspace, and storage. The Equinix Seattle Third Avenue data center offers colocation, interconnection and PAIX peering services.

LOCATION

Securities Building Technology Center
1914 Third Avenue,
Seattle, WA 98101, USA

PROFILE

Phone - 1.888.892.0607 (USA or Canada)
or 1.650.513.7600 (outside USA or Canada)
Email - support@equinix.com

POWER

Power Density - 4.0KW Max (utilization)

UPS System - 450 KW UPS System, System is deployed as N + 1, UPS Battery backup systems are deployed to carry full design load for 15 minutes, UPS distribution systems support 450 KW primary with 30% additional for redundant circuits.

DC Plant - 173 KW DC System, System is deployed as N+1 with dedicated A&B plants, DC Battery backup system are designed and deployed to carry full load for 2 hours per each plant, DC distribution systems support 173 KW primary with 30% additional for redundant circuits.

Standby Generators - 1500 KW generator systems, System is deployed as N, Dedicated fuel system designed and deployed to sustain continuous operation at full design load for 24 hours.

FIBER

Fiber - Fiber Diversity

TELCO INFORMATION

NPA/NXX - 206-344, 233

ENVIRONMENT

Fire Supression - Pre-Action double interlock fire suppression system, dual zoned smoke and heat fire alarm detection system, dry Pipe water based system, cross zone releasing function (three events must occur for full release) re-action, dry pipe sprinkler system

HVAC - 1055 KW of Heat Rejection Capacity, System is deployed as N+1, A/C units maintain a climate of 70 degrees (+/- 5) and 30-60% humidity, (SLA Statement)

Alarm Monitoring - All essential equipment is tied into Falcon Alarm System (UPS, DC plant, PMM's, BDCBB's, ATS's, Generators, Diesel Tanks, TVSS, Fire system), Operations Alarm Management (OAM) Group Monitors facility falcon units 24/7/365, Alarming is a dry contact system set to normally closed.

LOCATION TECHNICAL SPECIFICATION

SEATTLE - 1914 3RD

FLOOR LOAD

Raised flooring, 250 pounds per square foot

CEILING HEIGHT

Ten feet above raised floor

ELEVATORS

Weight capacity at 6,000 pounds; dimensions at 10x15x8 feet

ROOF RIGHTS

Roof rights available

LINE OF SIGHT

Clear line of sight in all directions

SQUARE FOOTAGE

Colocation Area - 19,138 sq. ft.

KVM CART

KVM cart available upon request

PRODUCT AVAILABILITY

Cage Space available
Cabinets Available
UPS Power Available
DC Power Available
Standard Cross Connects – DS0, DS1, DS3, Ethernet, Fiber
Metro Cross Connects – Ethernet, GigE
PAIX Ports- Port speeds from: 100mbps, GigE, to 10GigE and bonded 10GigE
SingleCNXT-i (Internet Access)
TechSmart (remote hands): 24/7/365
Technical Support
Network Timing: GPS (primary) and CDMA (redundant) time source

SECURITY

Security Systems – Card access control at all secure areas/doors, Surveillance cameras at strategic locations, exterior and interior CCTV coverage, 24/7 Corporate security surveillance, Speaker and Phone system installed throughout facility for correspondence with local and remote security personnel, 30 days of on-site video back-up

PUBLIC PEERING

This location offers Switch and Data PAIX Services and is connected to the Westin Bldg. PAIX

EQUINIX MMR

AboveNet, Cogent, Frontier Communications of America, Level (3), MCI, Qwest, SingleCNXT, WilTel, Yipes