

TAMPA



ABOUT

The Equinix Tampa data center is located within The Franklin Exchange, a twenty-two-story landmark building in downtown Tampa. Strategically located, Franklin Exchange occupies a full city block and is in the vicinity of ITC Deltacom, Florida Digital Network and Park Tower, another major Tampa telco hotel. The Equinix Tampa colocation data center offers more than 13,000 square feet of space with multiple connectivity and interconnection options. This site offers roof rights with satellite space and diverse fiber entry points.

LOCATION

655 North Franklin Street
The Franklin Exchange
Tampa, FL 33602, USA

PROFILE

Phone – 1.888.892.0607 (USA or Canada)
or 1.650.513.7600 (outside USA or Canada)
Email – support@equinix.com

POWER

Power Density – 2.4KW Max (utilization)

UPS System – 304 KW UPS System, System is deployed as N + 1, UPS Battery backup systems are deployed to carry full design load for 15 minutes, UPS distribution systems support 304 KW primary with 30% additional for redundant circuits.

DC Plant – 115 KW DC System, System is deployed as N+1 with dedicated A&B plants, DC Battery backup system are designed and deployed to carry full load for 2 hours per each plant, DC distribution systems support 115 KW primary with 30% additional for redundant circuits.

Standby Generators – 750 KW generator systems, System is deployed as N, Dedicated fuel system designed and deployed to sustain continuous operation at full design load for 24 hours.

FIBER

Fiber Entry Points – 2
Fiber Conduits – Eight 4-inch conduits
Fiber Innerducts – Thirty-two innerducts and four 1-inch innerducts/conduit

TELCO INFORMATION

NPA/NXX – 813-387

ENVIRONMENT

Fire Supression – Pre-Action double interlock fire suppression system, dual zoned smoke and heat fire alarm detection system, dry Pipe water based system, cross zone releasing function (three events must occur for full release) re-action, dry pipe sprinkler system

HVAC – 492 KW of Heat Rejection Capacity, System is deployed as N+1, A/C units maintain a climate of 70 degrees (+/- 5) and 30-60% humidity, (SLA Statement)

Alarm Monitoring – All essential equipment is tied into Falcon Alarm System (UPS, DC plant, PMM's, BDCBB's, ATS's, Generators, Diesel Tanks, TVSS, Fire system), Operations Alarm Management (OAM) Group Monitors facility falcon units 24/7/365, Alarming is a dry contact system set to normally closed.

TAMPA

FLOOR LOAD

125 pounds per square foot

CEILING HEIGHT

11 feet above raised flooring

ELEVATORS

Weight capacity at 3,000 pounds and dimensions at 4 x 5 x 10 feet. Prior notification necessary for use

ROOF RIGHTS

Roof rights available with satellite space

LINE OF SIGHT

Clear line of sight to the north and east with partially obstructed view to the south and west

SQUARE FOOTAGE

Colocation Area - 13,159 sq. ft.

KVM CART

KVM cart available upon request

PRODUCT AVAILABILITY

Cage Space available
Cabinets Available
UPS Power Available
DC Power Available
Standard Cross Connects – DS0, DS1, DS3, Ethernet, Fiber
SingleCNXT-i (Internet Access)
TechSmart (remote hands): 24/7/365
Technical Support
Network Timing: GPS (primary) and CDMA (redundant) time source

SECURITY

Security Systems – Card access control at all secure areas/doors, Surveillance cameras at strategic locations, exterior and interior CCTV coverage, 24/7 Corporate security surveillance, Speaker and Phone system installed throughout facility for correspondence with local and remote security personnel, 30 days of on-site video back-up

EQUINIX MMR

AT&T/TCG, Cogent Communications, FPL Fibernet, Level (3), MCI, SingleCNXT, Time Warner Telecom, Verizon, DeltaCom, Fiberlight, XO Communications

