

TORONTO



ABOUT

Originally built in 1954 to house telegraph equipment; by 2001 98% of 151 was conditioned for telecommunications tenants and today is Toronto's premier carrier hotel.

LOCATION

151 Front Street,
Toronto, Ontario M5J2N1, Canada

PROFILE

Phone – 1.888.892.0607 (USA or Canada)
or 1.650.513.7600 (outside USA or Canada)
Email – support@equinix.com

POWER

Power Density – 2.4KW Max (utilization)

UPS System – 2160 kW UPS System, System is deployed as N+1, UPS battery backup systems are designed and deployed to carry full design load for 15 minutes, UPS distribution systems supports 2160 kW primary with 30% additional for redundant circuits.

DC Plant – 144 kW DC system, System is deployed as 2N +1 with dedicated A & B plants, DC battery backup systems are designed and deployed to carry full design load for 2 hours per each plant, DC distribution systems supports 144 kW primary with 50% additional for redundant circuits.

Standby Generators – 4000 kW generators system, Systems is deployed as N, Dedicated fuel system designed and deployed to sustain continuous operation at full design load for 24 hours. .

FIBER

Fiber Conduits – Connectivity conduits are from existing Switch and Data Services throughout the building

TELCO INFORMATION

NPA/NXX – 416

ENVIRONMENT

Fire Supression – Pre-Action double interlock fire suppression system, dual zoned smoke and heat fire alarm detection system, dry Pipe water based system, cross zone releasing function (three events must occur for full release) re-action, dry pipe sprinkler system

HVAC – 2304 KW of Heat Rejection Capacity, System is deployed as N+1, A/C units maintain a climate of 70 degrees (+/- 5) and 30-60% humidity, (SLA Statement)

Alarm Monitoring – All essential equipment is tied into Falcon Alarm System (UPS, DC plant, PMM's, BDCBB's, ATS's, Generators, Diesel Tanks, TVSS, Fire system), Operations Alarm Management (OAM) Group Monitors facility falcon units 24/7/365, Alarming is a dry contact system set to normally closed.

TORONTO

FLOOR LOAD

200 pounds per square foot

CEILING HEIGHT

11 feet above raised flooring

ELEVATORS

Weight capacity at 5,000 pounds

ROOF RIGHTS

Roof rights available

LINE OF SIGHT

Clear line of sight in all directions

SQUARE FOOTAGE

Colocation Area - 58,826 sq. ft.

KVM CART

KVM cart available upon request

PRODUCT AVAILABILITY

Cage Space available
Cabinets Available
UPS Power Available
DC Power Available
Standard Cross Connects – DS0, DS1, DS3,
Ethernet, Fiber
SingleCNXT-i (Internet Access)
TechSmart (remote hands): 24/7/365
Technical Support
Roof Space
Network Timing: GPS (primary) and
CDMA (redundant) time source

SECURITY

Security Systems – Card access control at all secure areas/doors, Surveillance cameras at strategic locations, exterior and interior CCTV coverage, 24/7 Corporate security surveillance, Speaker and Phone system installed throughout facility for correspondence with local and remote security personnel, 30 days of on-site video back-up

EQUINIX MMR

360 Networks, Allstream Networks, AT&T, Bigpipe, Bell Canada, Bell Nexia, Cogent Communications, Equant, Global Crossing, Group Telecom, HydroOne, Telecom, Level3, Limelight Networks, MCI, Primus Telecom, Q9, Rogers Telecom, Saskatchewan Telecommunications, SingleCNXT, T-Systems, Teleglobe, Telus, ToriX, Videotron.

BUILDING MMR

Toronto Hydro, Hydro One, Peer1, Rogers

