

VIENNA – 8502 TYCO



ABOUT

Equinix is located within three buildings in the Washington D.C. metro area. We are at 11513-19 Sunset Hills Road in Reston and at 8502-A Tyco Road and 7990 Science Applications Court in Vienna, all located in the dominant fiber corridor of the Vienna/Tyson's Corner area. The Tyco Road location is a one-story warehouse building offering more than 24,000 square feet of colocation space, multiple connectivity options and several layers of security.

LOCATION

8502-A Tyco Road
Vienna, VA 22182, USA

PROFILE

Phone – 1.888.892.0607 (USA or Canada)
or 1.650.513.7600 (outside USA or Canada)
Email – support@equinix.com

POWER

Power Density – 4.0KW Max (utilization)

UPS System – 405 KW UPS System, System is deployed as N + 1, UPS Battery backup systems are deployed to carry full design load for 15 minutes, UPS distribution systems support 405 KW primary with 30% additional for redundant circuits.

DC Plant – 60 KW DC System, System is deployed as N+1 with dedicated A&B plants, DC Battery backup system are designed and deployed to carry full load for 2 hours per each plant, DC distribution systems support 60 KW primary with 30% additional for redundant circuits.

Standby Generators – 750 KW generator systems, Systems is deployed as N, Dedicated fuel system designed and deployed to sustain continuous operation at full design load for 24 hours. .

FIBER

Fiber Entry Points – 2

Fiber Conduits – Six 4-inch conduits

Fiber Innerducts – Twenty-four innerducts and four 1-inch innerducts/conduit

TELCO INFORMATION

NPA/NXX – 703-893

ENVIRONMENT

Fire Supression – Pre-Action double interlock fire suppression system, dual zoned smoke and heat fire alarm detection system, dry Pipe water based system, cross zone releasing function (three events must occur for full release) re-action, dry pipe sprinkler system

HVAC – 492 KW of Heat Rejection Capacity, System is deployed as N+1, A/C units maintain a climate of 70 degrees (+/- 5) and 30-60% humidity, (SLA Statement)

Alarm Monitoring – All essential equipment is tied into Falcon Alarm System (UPS, DC plant, PMM's, BDCBB's, ATS's, Generators, Diesel Tanks, TVSS, Fire system), Operations Alarm Management (OAM) Group Monitors facility falcon units 24/7/365, Alarming is a dry contact system set to normally closed.

VIENNA - 8502 TYCO

FLOOR LOAD

200 pounds per square foot

CEILING HEIGHT

Twelve feet above raised flooring

ROOF RIGHTS

Roof rights available with satellite space

LINE OF SIGHT

Clear line of sight in all directions

SQUARE FOOTAGE

Colocation Area - 24,576 sq. ft.

KVM CART

KVM cart available upon request

PRODUCT AVAILABILITY

Cage Space available
Cabinets Available
UPS Power Available
DC Power Available
Standard Cross Connects - DS0, DS1, DS3,
Ethernet, Fiber
SingleCNXT-i (Internet Access)
TechSmart (remote hands): 24/7/365
Technical Support
Roof Space
Network Timing: GPS (primary) and
CDMA (redundant) time source

SECURITY

Security Systems - Card access control at all secure areas/doors, Surveillance cameras at strategic locations, exterior and interior CCTV coverage, 24/7 Corporate security surveillance, Speaker and Phone system installed throughout facility for correspondence with local and remote security personnel, 30 days of on-site video back-up

EQUINIX MMR

AboveNet, Frontier Communications of America, Level (3), MCI, NEON, OnFiber Communications, Qwest, SingleCNXT, Verizon, WilTel, XO Communications, Yipes